



Hula 46. Barstool with upholstered seat or oak wood and injection swivel central base finished in different colors.

0.22 m3 7.77 Ft 6.7 kg 14.77 Lbs

	Backrest height	Seat height	Width	Depth
Measures (mm)	760	830	480	460

Frame	Injected aluminium swivel central base. Rotating system integreted into top of the structure. Injected aluminum plate fixes the base to the seat. Felt glides.
Seat	Upholstered seat with flame retardant polyurethane flexible foam with a density between 25 kg/m3 and 40 kg/m3, oak or walnut wood.
Accesories	Felt glide.
Other materials	Zinc-nickel electrolyte screws. Galvanized staples. Polyvinyl acetate glue.
Leather	Leather / Piel L1 High grade cow leather Piel de vaca de 1ª categoría L3 Polished full grain leather Plena flor pulida L6 Aniline leather batique-effect. Scandinavian cattle. Piel anilina efecto batique. Ganado escandinavo.

Premium finish
 and wood
 lacquers



Wood finish Oak



Aluminum finish



RESISTANCE AND QUALITY	UNE-EN 16139:2013
FIREPROOF	UNE-EN 1021-1:2006 B.S. 5852 Part 2 Crib V California Tech.Bulletin 117 BKZ 5.2
SUSTAINABILITY	FSC ISO 14001 level® 2 certified to ANSI/BIFMA e3 Standard